.XOM-25121D1



12.1" Open Frame Monitor

Overview

The Intronix Systems Open Frame Monitor series features a modular design that allows for versatile installation using both back and VESA methods. With its borderless design and lightweight construction, this series can seamlessly integrate into any embedded application. Additionally, the open architecture supports a size range of 8 to 15.6 inches and offers multiple touch screen options, including resistive and capacitive technologies.

Features

- HDMI/DP, VGA, DVI three signal interfaces
- Multiple installation methods including rear installation and VESA installation
- Solution for resistive/capacitive touch screen
- DC-IN 12 to 24V









I/O Interfaces



.XOM-25121D1



12.1" Open Frame Monitor

Specifications


| DISPLAY | |
|---------------------------|---|
| Size | 12.1-inch |
| Size | Projected capacitive multitouch |
| Touch type | 5-wire resistive touch (optional) |
| Transmittance | 87% (Capacitive) |
| | 80% (Resistive) |
| Control interface | USB |
| Control interface | ≥7H |
| Surface hardness | ≥3H |
| Resolution | 1024 x 768 |
| Luminance | 450 nits |
| Contrast ratio | 1000: 1 |
| View angles | 80 (left), 80 (right), 80 (up), 80 (down) |
| LED Lifetime | 50 000 hrs |
| Color | 16.7M |
| I/O PORTS | 10.711 |
| USB | 1x USB 2.0 |
| 035 | 1x HDMI |
| Display | 1x VGA |
| | 1x DVI |
| POWER | IX DVI |
| Button | Yes |
| DC Input | 12 to 24 VDC |
| Power Connector | 2-pin Phoenix terminal |
| Power Consumption | 10W |
| Power Adaptor | AC-DC, 12V, 5A, 60W |
| ENVIRONMENT | AC DC, 12V, 3A, 00VV |
| Operating temperature | -10°C to 50°C (14°F to 122°F) |
| Storage temperature | -20°C to 60°C (-4°F to 140°F) |
| Relative humidity | 10% to 95% @ 40°C (104°F), non-condensing |
| Vibration | 5 to 500Hz, 0.026 G ² /Hz, 2.16 Grms, X, Y, Z, 1 hour per axis |
| IP Rating | IP65 compliant (For Front Panel) |
| MECHANICAL | 11 03 compliant (1 of 1 font 1 affet) |
| | 311.6 x 240 x 34.5 mm (12.2 x 9.4 x 1.4 inches) |
| Dimensions (W x D x H mm) | 318 x 256 x 36 mm (12.5 x 10.1 x 1.42 inches)(Including touch solution) |
| Weight (kg) | 2.2 kg (4.8 lbs) |
| | 2.45 kg (5.4 lbs) (Including touch solution) |
| Mounting | Wall mount bracket VESA 75 |
| | Aluminum alloy panel |
| Material | All-metal chassis |
| CERTIFICATION | |
| | CE |
| EMC | FCC |
| PACKING LIST | |
| Packing | 1x XOM-25121D1 |
| | 1x Warranty card |
| | |


.XOM-25121D1



12.1" Open Frame Monitor

Dimensions





Ordering Information

| Ref. | Description |
|--------------|--|
| XOM-25121D1R | 12.1" LCD Industrial Monitor with resistive touch, DC12-24V input, Phoenix 2P TB |
| XOM-25121D1C | 12.1" LCD Industrial Monitor with P-CAP touch, DC12-24V input, Phoenix 2P TB |