## .XIM-23121D1



12.1" Industrial Touch Monitor with Capacitive or Resistive Touch Screen

#### **Overview**

The XIM-23121D1 is an 12.1-inch 4:3 industrial monitor designed for industrial applications. It features a projected capacitive multitouch or 5-wire resistive touchscreen, housed within a highly durable metal casing, providing front panel IP65-rated protection from water and dust ingress. It supports three signal interfaces via VGA, DP/HDMI, and DVI. Furthermore, the ultra-thin design of the XIM-23121D1 enables both VESA 100 mount and panel mount installation, simplifying the installation process in different applications.

#### **Features**

- 12.1" LED-backlit LCD with capacitive or resistive touch screen
- 1x VGA, 1x DVI, 1x DP/HDMI, 1x USB2.0
- DC-IN 12 to 24V
- Supports VESA 100 mount and panel mount
- IP65 compliant front panel









Touch display

#### **I/O Interfaces**



# .XIM-23121D1



12.1" Industrial Touch Monitor with Capacitive or Resistive Touch Screen

## **Specifications**


DISPLAY	
Size	12.1-inch
	Projected capacitive multitouch
Touch type	5-wire resistive touch (optional)
_	87% (Capacitive)
Transmittance	80% (Resistive)
Control interface	USB
	≥7H
Surface hardness	≥3H
Resolution	1024 x 768
Luminance	450 nits
Contrast ratio	1000: 1
View angles	80 (left), 80 (right), 80 (up), 80 (down)
LED Lifetime	50 000 hrs
Color	16.7M
I/O PORTS	10.711
USB	1x USB 2.0
USB	
Display	1x DP / HDMI (select one) 1x VGA
	1x DVI
POWER	IX DVI
Button	Yes
	12 to 24 VDC
DC Input	
Power Connector	Button
Power Consumption	10W
Power Adaptor	AC-DC, 12V, 5A, 60W
ENVIRONMENT	4000 + 5000 (4405 + 40005)
Operating temperature	-10°C to 50°C (14°F to 122°F)
Storage temperature	-20°C to 60°C (-4°F to 140°F)
Relative humidity	10% to 95% @ 40°C (104°F), non-condensing
Vibration	5 to 500Hz, 0.026 G <sup>2</sup> /Hz, 2.16 Grms, X, Y, Z, 1 hour per axis
IP Rating	IP65 compliant (For Front Panel)
MECHANICAL	
Dimensions (W x D x H mm)	310 x 248 x 41.5 mm (12.2 x 9.7 x 2.4 inches)
Weight (kg)	2.45 kg (8.3 lbs)
Mounting	Panel mount
	Wall mount bracket VESA 100
Material	Aluminum alloy panel
	All-metal chassis
CERTIFICATION	
EMC	CE
	FCC
PACKING LIST	
	1x XIM-23121D1
Packing	6x Panel mounting buckles
	1x Warranty card

# .XIM-23121D1



12.1" Industrial Touch Monitor with Capacitive or Resistive Touch Screen

## **Dimensions**



## **Ordering Information**

Ref.	Description
XIM-23121D1R	12.1" LCD Industrial Monitor with resistive touch, DC12-24V input, Phoenix 2P TB
XIM-23121D1C	12.1" LCD Industrial Monitor with P-CAP touch, DC12-24V input, Phoenix 2P TB